

FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency integral reflector combined with opal lens insert provide excellent lighting distribution.
- ✓ Square internal louver is available in a wide range of finishes.
- ✓ Aluminum body of the luminaire comes with built-in-driver.
- ✓ Suitable for surface mounted installations.
- ✓ LED Spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

TYPE

- ☐ 1-Single
- ☐ 2-Double
- ☐ 3-Triple

DRIVER

- ☐ ST - Standard
- ☐ DT - ELV
- ☐ DL - 0-10V Dimming (1%)
- ☐ *

* Please specify dimming method.

LOUVER

- ☐ WH - White
- ☐ BK - Black
- ☐ SL - Silver
- ☐ GL - Gold
- ☐ RG - Rose Gold

CCT

- ☐ 30K - 3000Kelvin
- ☐ 35K - 3500Kelvin
- ☐ 40K - 4000Kelvin
- ☐ DW - Dim to Warm

*Other options are available.

SOURCE

- ☐ 10W LED
- ☐ 15W LED

MOUNTING

- ☐ SF - Surface Mount

FINISH

- ☐ WH - White
- ☐ BK - Black
- ☐ GR - Grey

OPTIONS

- ☐ No Options*
- ☐ 90 CRI

*Leave Empty.

VOLTAGE

- ☐ 120V
- ☐ 277V
- ☐ 347V*


* Not available for all configurations.

LUMEN OUTPUT:

Watts	30K	35K	40K
10W	930 lm	950 lm	970 lm
15W	1395 lm	1425 lm	1450 lm

DIMENSIONS:

Unit	Length	Height	Width
Single	3.750"	4.500"	3.750"
Double	7.375"	4.500"	3.750"
Triple	10.937"	4.500"	3.750"



SPECIFICATION:

ED CUBIX+ TYPE x SOURCE - VOLTAGE - DRIVER - MOUNTING - LOUVER - FINISH - CCT - OPTIONS

Enter the Product Code into the boxes above.

Project:

Type: