



FEATURES:

- Architectural luminaire with direct-indirect lighting distribution.
- Light source: LED Strips.
- Diffused illumination is provided by two opal frosted polycarbonate round domes.
- Suitable for non insulated recessed installations in to T-bar or drywall.
- Fixture body is made from light weight steel in white finish.
- LED Strips are rated for 60,000hrs. L70 and +85CRI.
- Has a proven record in office, commercial and retail applications.
- Custom modifications are available.
- ED luminaires are certified to CSA and UL standards.


SPECIFICATION: ED MLT+

SOURCE	VOLTAGE	DRIVER	MOUNTING	CCT
30W LED	120V	ST - Standard	RS - Recessed	30K - 3000Kelvin
40W LED	277V	DL - 0.10V Dimming	DR - Drywall	35K - 3500Kelvin
	347V*	DM - Dimming**		40K - 4000Kelvin

* Not available for all configurations.
 ** Please specify dimming requirements.

DIMENSIONS:

Length: 23 3/4"
 Width: 23 3/4"
 Depth: 3 "



LUMEN OUTPUT:

Watts	30K	35K	40K
30W	3120 lm	3200 lm	3280 lm
40W	4150 lm	4250 lm	4350 lm

Project:

Type:

Edison Lighting Group Ltd.

1303 Ringwell Dr. Unit #2, Newmarket, ON L3Y 8T9
 Tel: 905-830-0339 or 1-800-667-9281 Fax: 905-898-6439 or 1-800-667-9302
 www.edisonlighting.ca info@edisonlighting.ca