# Edison

## **ED MRT+**







#### **FEATURES:**

- Architectural luminaire with direct lighting distribution.
- Light source: COB LED.
- High efficiency Jordan Alunova integral reflector is available with Spot 17°, Flood 24° or Wide Flood 40° light distribution.
- Enlarge round trim directs the light and reduces the glare.
- Spot and driver enclosure are available in white or black finish.
- Comes standard with Global Track adapter.
- LED Spot is rated for 60,000hrs. L70 and +85CRI.
- Has a proven record in office, commercial and retail applications.
- Custom modifications are available.
- ED luminaires are certified to CSA and UL standards.

## **SPECIFICATION: ED MRT+**


SOURCE	VOLTAGE	DRIVER	MOUNTING	REFLECTOR	FINISH	ССТ
15W LED	120V	ST - Standard	GT - Global Track	SP - Spot	WH - White	30K - 3000Kelvin
20W LED	277V			FL - Flood	BK - Black	35K - 3500Kelvin
				WF - Wide Flood		40K - 4000Kelvin

### **DIMENSIONS:**

Width: 13 5/8" Height: 8 7/8" Diameter: 5 1/4"

## **LUMEN OUTPUT:**

Watts	30K	35K	40K
15W	1685 lm	1725 lm	1765 lm
20W	2250 lm	2300 lm	2350 lm



Project:		
Type:		


## Edison Lighting Group Ltd.




# TRAC SYSTEM

## PROFILE CROSS CUT AND DIMENSIONS:

Surface








<b>Profile:</b>	w	d
Surface	1 1/4"	1 1/2"
Recessed	21/4"	1 1/2"

## **SIZES AND FINISH OPTIONS:**

Length	Finish options		
	Surface	Recessed	
2 Feet	WH-White BK-Black	WHR-White RS BKR-Black RS	
4 Feet	WH-White BK-Black	WHR-White RS BKR-Black RS	
6 Feet	WH-White BK-Black	WHR-White RS BKR-Black RS	
8 Feet	WH-White BK-Black	WHR-White RS BKR-Black RS	

## LINEAR COUPLER:



### **FEED JUNCTIONS AND ACCESSORIES:**

Left Live End



Right Live End



Live Middle Feed



L-Feed



T-Feed



X-Feed




Dead End



Linear coupler



Flexible connector



T-bar clamp

