



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency integral reflector combined with opal lens insert provide excellent lighting distribution.
- ✓ Available with Spot 25°, Flood 45° and Wide Flood 60° beam angle.
- ✓ Aluminum body of the luminaire comes with built-in-driver.
- ✓ Suitable for suspended installations.
- ✓ LED Spot is rated for 60,000hrs. L70 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED PIPE+

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	REFLECTOR	FINISH	CCT	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Enter the Product Code into the boxes above.

SOURCE

- ☐ 10W LED
- ☐ 15W LED
- ☐ 20W LED

RADIANCE

- ☐ DD - Direct (100%Down)
*Light Distribution.

VOLTAGE

- ☐ 120V
- ☐ 277V

DRIVER

- ☐ ST - Standard
- ☐ DL - 0-10V Dimming
- ☐ DT - TRIAC
- ☐ *

* Please specify dimming method.

MOUNTING

- ☐ S4 - Suspension 4Feet
- ☐ S6 - Suspension 6Feet
- ☐ S Feet*

* Please specify required Length.

REFLECTOR

- ☐ SP - Spot
- ☐ FL - Flood
- ☐ WF - Wide Flood

FINISH

- ☐ WH - White
- ☐ BK - Black
- ☐ GR - Grey

CCT

- ☐ 30K - 3000Kelvin/90CRI
- ☐ 35K - 3500Kelvin/90CRI
- ☐ 40K - 4000Kelvin/90CRI

*Other options are available.

OPTIONS

- ☐ No Options*
- ☐ CB - Casambi BT


*Leave Empty.

DIMENSIONS:

Width	Height	Canopy
4.0"	11.0"	5.0"

LUMEN OUTPUT:

Watts	30K	35K	40K
10W	930 lm	950 lm	990 lm
15W	1395 lm	1425 lm	1475 lm
20W	1860 lm	1900 lm	1940 lm



Project:

Type: