



## FEATURES:

- ✓ Architectural luminaire with direct/indirect lighting distribution.
- ✓ Light source: COB LED.
- ✓ Extremely durable round diffuser is made from frosted PMMA Polycarbonate for even lighting distribution.
- ✓ Steel body is available with white or black finish.
- ✓ Suitable for surface and wall mounted installations.
- ✓ LED spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

## SPECIFICATION:

**ED COR+**

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	LENS	FINISH	CCT	OPTIONS

Enter the Product Code into the boxes above.

### SOURCE

- ☐ 15W LED
- ☐ 20W LED
- ☐ 30W LED

### RADIANCE

- ☐ DI - Direct Indirect (85%DN/15%Up)

\*Light Distribution.

### VOLTAGE

- ☐ 120V
- ☐ 277V
- ☐ 347V\*

\*Not available for all configurations.

### DRIVER

- ☐ ST - Standard
- ☐ DL - 0-10V Dimming (1%)
- ☐ DA - DALI
- ☐ \*

\* Please specify dimming method (ELV).

### MOUNTING

- ☐ WM -Wall Mount
- ☐ CM-Ceiling Mount

### LENS

- ☐ OP - Opal

### FINISH

- ☐ WH - White
- ☐ BK - Black
- ☐ GR - Grey

### CCT

- ☐ 30K - 3000Kelvin
- ☐ 35K - 3500Kelvin
- ☐ 40K - 4000Kelvin
- ☐ TW - Tunable White\*\* (2700K-6500K)

\*Other options are available.

\*\*Available with Dali controls.

### OPTIONS

- ☐ No Options\*
- ☐ 90 CRI


\*Leave Empty.

## DIMENSIONS:


Height	Width
2.375"	11.5"

## LUMEN OUTPUT:

Watts	30K	35K	40K
15W	1360 lm	1400 lm	1440 lm
20W	1850 lm	1900 lm	1950 lm
30W	2800 lm	2900 lm	3000 lm



W



h

Project:

Type: