

## FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency integral reflector combined with opal lens insert provide excellent lighting distribution.
- ✓ Square internal louver is available in a wide range of finishes.
- ✓ Aluminum body of the luminaire comes with built-in-driver.
- ✓ Suitable for suspended and surface mounted installations.
- ✓ LED Spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

### SOURCE

- 15W LED
- 20W LED
- 25W LED

### DRIVER

- ST - Standard
- DT - ELV
- DL - 0-10V Dimming (1%)
- \*

\* Please specify dimming method.

### LOUVER

- WH - White
- BK - Black
- SL - Silver
- GL - Gold
- RG - Rose Gold

### CCT

- 30K - 3000Kelvin
- 35K - 3500Kelvin
- 40K - 4000Kelvin
- DW - Dim to Warm

\*Other options are available.

### RADIANCE

- DD - Direct (100%Down)

\*Light Distribution.

### MOUNTING

- SF - Surface Mount
- S4 - Suspension 4Feet
- S6 - Suspension 6Feet
- S  Feet\*

\* Please specify required Length.

### FINISH

- WH - White
- BK - Black
- GR - Grey

### OPTIONS

- No Options\*
- 90 CRI

\*Leave Empty.

### VOLTAGE

- 120V
- 277V
- 347V\*


\* Not available for all configurations.

### LUMEN OUTPUT:

Watts	30K	35K	40K
15W	1400 lm	1430 lm	1460 lm
20W	1910 lm	1950 lm	1990 lm
25W	2350 lm	2400 lm	2450 lm

### DIMENSIONS:

Width	Height
4.5"	6.0"



Project: \_\_\_\_\_

Type: \_\_\_\_\_

### SPECIFICATION:

ED CUBIC+  -  -  -  -  -  -  -  -  -

Enter the Product Code into the boxes above.