


FEATURES:

- ✓ Architectural luminaire with direct distribution.
- ✓ Light source: LED strips.
- ✓ Diffused illumination is provided by high efficiency opal lens.
- ✓ Distinctive shape and magnetic sides of the luminaire provide tool free option is used as a building block to create unique design forms.
- ✓ Extruded aluminum body comes with white, black or grey finish.
- ✓ Also available with custom color options or vinyl decals.
- ✓ LED Strips are rated for 60,000hrs. L80 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight
SPECIFICATION:

ED MILA+ SOURCE — RADIANCE — VOLTAGE — DRIVER — MOUNTING — LENS — FINISH — CCT — OPTIONS

Enter the Product Code into the boxes above.

SOURCE

- 20WLED
- 40WLED

RADIANCE

- DD - Direct (100%Down)
- *Light Distribution.

VOLTAGE

- 120V
- 277V
- 347V*

*Not available for all configurations.

DRIVER

- ST - Standard
- DL - 0-10V Dimming (1%)
- DA - DALI
- *

* Please specify dimming method (ELV).

MOUNTING

- S4-Suspension 4Feet
- S6-Suspension 6Feet
- S Feet*
- WM - Wall Mount
- SF - Surface Mount

*Please specify required Length.

LENS

- OP - Opal

FINISH

- WH - White
- BK - Black
- GR - Grey
- CF - Custom RAL#
- VD - Vinyl Decal*

* Please provide 600dpi Image.

CCT

- 30K - 3000Kelvin
- 35K - 3500Kelvin
- 40K - 4000Kelvin
- TW - Tunable White** (2700K-6500K)

*Other options are available.

**Available with Dali controls.

OPTIONS

- No Options*
- 90 CRI
- DS-Daylight Sensor
- DC - Dual Circuit**
- OS - Occupancy Sensor
- DOS - Daylight & Occupancy Sensor

*Leave Empty.

**Down /Up Control separately.

***Combination example (90CRI/DS).



LUMEN OUTPUT:

Watts	30K	35K	40K
20W	2100 lm	2125 lm	2200 lm
40W	4200 lm	4300 lm	4400 lm

Project:

Type:


SIZE:



Height	Width
2.750 Inch	17.50 Inch
L1	L2
40.75 Inch	9.750 Inch


RADIANCE:

DIRECT DISTRIBUTION



Keys	
1	3 x Magnet Sides
2	4 x Wago connectors
3	2 x SF Mountings
4	2 x SS Mountings


MOUNTING:




SURFACE MOUNT



SUSPENDED



CUSTOM



CUSTOM - INFINITY