

FEATURES:

- ✓ Architectural luminaire with direct or direct-indirect distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by high efficiency frosted opal lens.
- ✓ Suitable for surface, suspended and recessed installations.
- ✓ Extruded aluminum body comes with white, black or grey finish.
- ✓ Also available with custom color options or vinyl decals.
- ✓ LED Strips are rated for 60,000hrs. L80 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED RECTANGLE+

SIZE	SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	LENS	FINISH	CCT	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Enter the order code into the boxes above.

SIZE

- ☐ 1x2 Feet
☐ 1x3 Feet
☐ 1x4 Feet
☐ *

*Specify required size.

SOURCE

- ☐ 25WLED
☐ 50WLED

*Other Wattages are available.

RADIANCE

- ☐ DD - Direct (100%Down)
☐ ID - Indirect (100%Up)**
☐ UD - Uneven(70%Down/30%Up)**
☐ IL - In Lit
☐ OL - Out Lit

*Light Distribution.

**Suspended Configuration only.

VOLTAGE

- ☐ 120V
☐ 277V
☐ 347V*

*Not available for all configurations.

DRIVER

- ☐ ST - Standard
☐ DL - 0-10V Dimming (1%)
☐ DA - DALI
☐ *

* Please specify dimming method (ELV).

MOUNTING

- ☐ S4-Suspension 4Feet
☐ S6-Suspension 6Feet
☐ S Feet*
☐ WM - Wall Mount
☐ SF - Surface Mount
☐ RT - Recessed Trimless

*Please specify required Length.

LENS

- ☐ OP - Opal

FINISH

- ☐ WH - White
☐ BK - Black
☐ GR - Grey
☐ CF - Custom RAL#
☐ VD - Vinyl Decal*

* Please provide 600dpi Image.

CCT

- ☐ 30K - 3000Kelvin
☐ 35K - 3500Kelvin
☐ 40K - 4000Kelvin
☐ TW - Tunable White**
 (2700K-6500K)

*Other options are available.

**Available with Dali controls.

OPTIONS

- ☐ No Options*
☐ 90 CRI
☐ DS-Daylight Sensor
☐ DC - Dual Circuit**
☐ OS - Occupancy Sensor
☐ DOS - Daylight & Occupancy Sensor

*Leave Empty.

**Down /Up Control separately.


***Combination example (90CRI/DS).

LUMEN OUTPUT:

Watts	30K	35K	40K
25W	2610 lm	2650 lm	2690 lm
50W	5150 lm	5250 lm	5380 lm

Project:

Type:

SIZE:



Size	Width x Length
1x2 Feet	13.5x24.50 Inch
1x3 Feet	13.5x35.50 Inch
1x4 Feet	13.5x46.50 Inch

RADIANCE:
DIRECT DISTRIBUTION



100%

UNEVEN DISTRIBUTION


 30%
 70%

MOUNTING:


SURFACE MOUNT




SUSPENDED




WALL MOUNT



IN LIT



OUT LIT



RECESSED TRIMLESS