



FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 20° Spot, 40° Flood or 60° wide Flood Beam angle.
- ✓ Integrated TRIAC/ELV dimming driver is placed into sleek minimalistic body of the luminaire.
- ✓ Available in white and black finishes.
- ✓ Comes standard with Juno track adapter.
- ✓ LED spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards. **reinventlight**

SPECIFICATION:

ED TRS+

| SOURCE | VOLTAGE | DRIVER | MOUNTING | REFLECTOR | FINISH | CCT | OPTIONS |
|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |

Enter the Product Code into the boxes above.

SOURCE

- ☐ 10W LED

VOLTAGE

- ☐ 120V
☐ 277V

DRIVER

- ☐ ST - Standard
☐ DT - ELV/Dimming

MOUNTING

- ☐ JT-Juno Track
☐ *
- *Other track adapters are available.

REFLECTOR

- ☐ SP - Spot
☐ FL - Flood
☐ WF - Wide Flood

FINISH

- ☐ WH - White
☐ BK - Black
☐ GR - Grey

CCT

- ☐ 30K - 3000Kelvin
☐ 35K - 3500Kelvin
☐ 40K - 4000Kelvin
- *Other options are available.

OPTIONS


- ☐ No Options*
☐ 90 CRI
- *Leave Empty.

DIMENSIONS:

| Height | Width | Diameter |
|--------|--------|----------|
| 5.500" | 4.125" | 2.375" |

LUMEN OUTPUT:

| Watts | 30K | 35K | 40K |
|-------|--------|---------|---------|
| 10W | 950 lm | 1000 lm | 1050 lm |



Project:

Type: