



**FEATURES:**

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: LED Strip.
- ✓ Diffused illumination is provided by high efficiency opal insert or optional low glare microprismatic lens.
- ✓ Suitable for non insulated recessed installations in to T-Bar or drywall.
- ✓ Fixture body is made from light weight steel in white finish.
- ✓ LED spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

**SPECIFICATION:**

**ED CUBE+**  SOURCE —  VOLTAGE —  DRIVER —  MOUNTING —  LENS —  FINISH —  CCT —  OPTIONS

Enter the Product Code into the boxes above.

**SOURCE**

- 25W LED
- 35W LED

**VOLTAGE**

- 120V
  - 277V
  - 347V\*
- \* Not available for all configurations.

**DRIVER**

- ST - Standard
- DL - 0-10V Dimming (1%)
- DA - DALI
- EM - Emergency
- \*

\* Please specify dimming method (ELV).

**MOUNTING**

- RS - Recessed
- DW - Dry Wall

**LENS**

- OP - Opal
- PR - Prismatic

**FINISH**

- WH - White
- BK - Black
- GR - Grey

**CCT**


- 30K - 3000Kelvin
- 35K - 3500Kelvin
- 40K - 4000Kelvin
- TW - Tunable White\*\* (2700K-6500K)

\*Other options are available.  
\*\*Available with Dali controls.

**OPTIONS**


- No Options\*
- 90 CRI
- DS - Daylight Sensor
- OS - Occupancy Sensor
- DOS - Daylight & Occupancy Sensor

\*Leave Empty.  
\*\*Combination example (90CRI/DS).



**DIMENSIONS:**

Length	Width	Height
23.75"	23.75"	1.625"



**LUMEN OUTPUT:**

Watts	30K	35K	40K
25W	2800 lm	2875 lm	2950 lm
35W	3925 lm	4025 lm	4125 lm

Project:

Type: