



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by high efficiency opal inserted or optional low glare microprismatic lens.
- ✓ Suitable for suspended and row mounted installations.
- ✓ Fixture body with integrated driver is made from light weight steel.
- ✓ Available with matt white, black or grey finishes.
- ✓ LED Strips are rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial applications.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SOURCE

- 35W LED
- 45W LED

VOLTAGE

- 120V
- 277V
- 347V*

*Not available for all configurations.

DRIVER

- ST - Standard
- DL - 0-10V Dimming (1%)
- DA - DALI
- *

* Please specify dimming method (ELV).

MOUNTING

- S4-Suspension 4Feet
- S6-Suspension 6Feet
- S Feet*
- SF - Surface Mount

*Please specify required Length.

LENS

- OP - Opal
- PR - Prismatic

FINISH

- WH - White
- BK - Black
- GR - Grey

CCT

- 30K - 3000Kelvin
- 35K - 3500Kelvin
- 40K - 4000Kelvin
- TW - Tunable White** (2700K-6500K)

*Other options are available.
**Available with Dali controls.

OPTIONS

- No Options*
- 90 CRI
- DS-Daylight Sensor
- DC - Dual Circuit**
- OS - Occupancy Sensor
- DOS - Daylight & Occupancy Sensor

*Leave Empty.
**Down /Up Control separately.
***Combination example (90CRI/DS).

DIMENSIONS:

Length	Width	Depth
47.25"	7.125"	2.250"

LUMEN OUTPUT:

Watts	30K	35K	40K
35W	3420lm	3500 lm	3580 lm
45W	4400 lm	4500 lm	4600 lm



Project: _____

Type: _____

SPECIFICATION:

ED EDGE+

SOURCE — VOLTAGE — DRIVER — MOUNTING — LENS — FINISH — CCT — OPTIONS

— — — — — — —

Enter the Product Code into the boxes above.