
FEATURES:

- ✓ Architectural luminaire with direct or indirect distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by high efficiency frosted opal lens.
- ✓ Suitable for surface, suspended and recessed installations.
- ✓ Extruded aluminum body comes with white, black or grey finishes.
- ✓ Also available with custom color options or vinyl decals.
- ✓ LED Strips are rated for 60,000hrs. L80 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SIZE

- 2x2x2 Feet
- 3x3x3 Feet
- 4x4x4 Feet
- *

*Specify required length.
 **Custom angles are available.

VOLTAGE

- 120V
- 277V
- 347V*

*Not available for all configurations.

LENS

- OP - Opal

CCT

- 30K - 3000Kelvin
- 35K - 3500Kelvin
- 40K - 4000Kelvin
- TW - Tunable White** (2700K-6500K)

*Other options are available.
 **Available with Dali controls.

SOURCE

- 25WLED
- 50WLED
- 75WLED*

* Available for 3 & 4 Feet.

DRIVER

- ST - Standard
- DL - 0-10V Dimming (1%)
- DA - DALI
- *

* Please specify dimming method (ELV).

FINISH

- WH - White
- BK - Black
- GR - Grey
- CF - Custom
- VD - Vinyl Decal*

* Please provide 600dpi Image.

OPTIONS

- No Options*
- 90 CRI
- DS - Daylight Sensor
- DC - Dual Circuit**
- OS - Occupancy Sensor
- DOS - Daylight & Occupancy Sensor

*Leave Empty.
 **Down /Up Control separately.
 ***Combination example (90CRI/DS).

RADIANCE

- DD - Direct (100%Down)
- ID - Indirect (100%Up)**
- IL - In Lite
- OL - Out Lite

*Light Distribution.
 **Suspended Configuration only.

MOUNTING

- S4 - Suspension 4Feet
- S6 - Suspension 6Feet
- S Feet*
- WM - Wall Mount
- SF - Surface Mount
- RT - Recessed Trimless

*Please specify required Length.

LUMEN OUTPUT:

Watts	30K	35K	40K
25W	2610 lm	2650 lm	2690 lm
50W	5150 lm	5250 lm	5380 lm
75W	7720 lm	7875 lm	8030 lm

Project:


Type:

SPECIFICATION:

ED TRIANGLE+ - - - - - - - - -

Enter the order code into the boxes above.

SIZE:



Size	LxW
2x2x2 Feet	22.86x26.40 Inch
3x3x3 Feet	32.39x37.40 Inch
4x4x4 Feet	41.92x48.40 Inch

RADIANCE:


DIRECT DISTRIBUTION




DIRECT DISTRIBUTION




MOUNTING:




SURFACE MOUNT




SUSPENDED



WALL MOUNT



RECESSED TRIMLESS



OUT-LITE



IN-LITE